

- Specification and General Notes:

 1. All components MMCD PLATINUM (Section 33 44 01) compliant and fabricated to CSA CERTIFICATE OF COMPLIANCE (ASTM C478M)
- All jurisdiction-specific components SUPPLEMENTAL to MMCD PLATINUM fabricated
- in accordance with CSA CERTIFICATE OF QUALIFICATION (CSA A23.4-09).
 Components certified to CSA standards (ASTM C478M & CSA A23.4-09) by approved 3. independent third party certification body accredited by Standards Council of Canada.
- All components marked with certification body logo and CSA standard markings.
- Testing to ASTM C497/CSA 23.1 & 2-09.
- 30 MPa MIN compressive strength (MAX 0.5 W/C ratio). Pipe penetrations to be grouted unless otherwise noted
- 25mm MIN concrete cover of reinforcing steel.
- 5mm manufacturing tolerance.
- 10. A-3 concrete exposure class
- 15MPa MIN stripping strength. 11.
- Standard grade form finish.
- Unformed steel trowel or wood float finish. 13.
- 3 point rigging to meet WORK SAFE BC OHS (Guideline 14/15) requirement 14.

5	Field	installation	and	testina	hν	others	
ي.	i icia	motanation	una	ccounty	<u> </u>	ouriers.	

BILL OF MATERIALS					
ITEM	DESCRIPTION	MASS KG	QUANTITY		
-	2448CBS	520	I		
2	D22B-Grate	48	I		
3	D-Traphood	10	I		
4	TRHDP	<	2		

	15. Ticla installation and testing by others.					
	•	Description:		Drawn :	Date :	
	DT A MOND	Ditch Catch Basin Type I		S.d.	20/09/2016	
	DI MOND			Aproved :	Load Rating:	
	PRECAST CONCRETE	CS - D - 8				
		Total district of the state of		Rev. No.	Scale :	
		Jurisdiction: City of Abbotsford			1:12	
	7520 Conrad Street Burnaby, B.C	520 Conrad Street Burnaby, B.C. V5A 2H7 Phone : 604-415-5181 Fax : 604-415-5185				

7520 Conrad Street

Phone: 604-415-5181 www: diamondconcrete.ca

I riis drawing is the property of the Diamond Precast Concrete. All information contained herein is confidential and may not be used in whole or in part without written permission from the owner

Sheet No. 1 OF 1

Catalog No.

Dwg. No. CoAbb-2